

Test for resistance to: ¹		Description: A measure of the ability of decorative overlaid surface		Typical Performance:	
				Solid Colors	Printed Patterns
WEAR		To maintain its design or color when subject to prolonged abrasive wear		700-900 cycles	125-200 cycles
	STAIN	To resist staining by prolonging contact with 15 common household substances ²		Tests 1-10: <i>No effect</i> Tests 11-15: <i>No effect to slight effect</i>	Tests 1-10: <i>No effect</i> Tests 11-15: <i>No effect to slight effect</i>
CLEANABILITY		To be cleaned following prolonged contact with 15 common household substances (High Pressure Laminate maximum allowed + 12)		10	10
	LIGHT	To retain its color after prolonged exposure to a light source having a frequency range approximating sunlight through windowglass		<i>No effect to slight effect</i>	<i>No effect to slight effect</i>
HIGH TEMPERATURE		To maintain its color and surface texture when subjected to a high temperature		<i>No effect to slight effect</i>	<i>No effect to slight effect</i>
	RADIANT HEAT	To resist any damage when subjected to a radiant heat source		<i>No effect after 80 sec. exposure</i>	<i>No effect after 80 sec. exposure</i>
BOILING WATER		To maintain its color and surface texture when subjected to boiling water		<i>No effect²</i>	<i>No effect²</i>

¹ NEMA LD-3-2005

² Dark colors may show a slight effect